



New SecurityShield 75 Manual Spec Sheet

# Specification Sheet

## SeceuroDoor 75c – Manual Industrial Shutter

### Common Applications

Industrial style steel roller shutter with scrolled slat profile. Suitable for commercial and industrial applications where power is not available.

### Minimum and Maximum sizes

<b>Minimum width</b>	<b>1000mm</b>
<b>Maximum width</b>	<b>5000mm</b>
<b>Minimum height</b>	<b>1000mm</b>
<b>Maximum height</b>	<b>5000mm</b>

### Lath

Construction: SeceuroDoor 75 uses a single skin scrolled solid steel lath  
SeceuroDoor Vision 75 uses a single skin scrolled perforated steel lath

Dimensions: Nominally 75mm high x 19mm thick  
20g 0.9mm thick  
22g 0.7mm thick

Weight: SeceuroDoor 75 – 10 or 12kg per square metre

Stock colours: Galvanised\*  
\* This product can be powder coated to an alternative standard RAL or BS colour at extra cost

### Bottom Slat

Construction: "T" sectioned steel bottom slat

Dimensions: "T" section - 49mm high x 74mm deep

Stock colours: Galvanised\*

Optional bullet locks - Not on wind guides

### Hood & Fascia

Construction: Two or three piece steel casing with steel end plates

Dimensions: To suit end plate (400,450)

Stock colours: Galvanised\*

**Guide Chennels**

Construction:	3mm galvanised steel channels
Dimensions:	65mm wide x 32mm deep 100mm wide x 32mm deep plain 65mm x 40mm windlock guides 100mm x 40mm windlock guides
Stock colours	Galvanised*

**Installation**

This product can be installed internally or externally

**Structural Material Minimum fixings**

Block or brickwork	o 8x75 Masonry Anchor
Steelwork	o M10 Bolts by appropriate length

The hood is fixed at each end and 1000mm centres

**Operations****Manual**

Manual operation is by a hand chain through cast gears. The door is counterbalanced with a spring & has a safety brake in case of spring failure.